



TEST REQUEST

- 1. 100% OPEN SHORT & MIS WIRE TEST
- 2. VOLTAGE: 300V INSULATION
- INSULATION RESISTANCE 10M Ohms MIN
- CONTACT RESISTANCE 5 Ohms MAX

PIN OUT:

P1	P2	P1	P2
1 RED (COAX)	1	9 PURPLE	9
6 DRAIN	6	5 RED	5
2 GREEN (COAX)	2	12 GREEN	12
7 DRAIN	7	10 BLUE	10
3 BLUE (COAX)	3	13 GRAY	13
8 DRAIN	8	11 ORANGE	11
4 BLACK	4	15 YELLOW	15
14 BROWN	14	shell	shell

7	OVER MOLD	PVC 45P BLACK	65	G
6	INSIDE-MOLD	PE NATURAL	10	G
5	SCREW	#4-40 T4.5*47 BLACK	4	PCS
4	CORE	17.5*9.5*28.5MM	1	PCS
3	CONN	HD15 FEMALE GOLD PLATED INSULATION BLACK	1	PCS
2	CONN	HD15 MALE GOLD PLATED INSULATION BLACK	1	PCS
1	CABLE	UL20276 3C*UL1354(S)+9C*28#+AL+D+B S=42±2/0.10±0.08MM 16*6/0.12±0.008 BLACK Jacket CL2 OD=9.0 MARKING:“MONOPRICE,Inc.”	0.915	M
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT



DESCRIPTION :
Monoprice™ Super VGA (SVGA) M/F Monitor Cable with Ferrite Cores, Gold Plated, 3ft

PID # :
2897

DATE :	UNIT : FT / IN / MM	FILE NAME:
--------	------------------------	------------