



8-Channel Speaker Zone Hub

P/N 38161

Quick Install Guide

INTRODUCTION

This 8-Channel Speaker Zone Hub is designed to connect up to eight pairs of speakers to a single amplifier or receiver. It uses removable terminal blocks for easy connection for the speaker wires. Note that this speaker selector does not include impedance matching circuitry, so the use of impedance matching volume controls are highly recommended to prevent damage to the amplifier caused by low impedance loads.

INSTALLATION

Perform the following steps to install this speaker selector.

1. Remove one of the black colored terminal blocks from the rear of the speaker selector.
2. Strip approximately 1/4" of insulation from each end of each speaker wire.
3. Using a small flathead screwdriver, loosen the screws on the terminal block.
4. Insert each end of the left channel positive speaker wire into the **L+** terminal and the negative speaker wire into the **L-** terminal, then tighten the screws to secure them in place.
5. Insert each end of the right channel positive speaker wire into the **R+** terminal and the negative speaker wire into the **R-** terminal, then tighten the screws to secure them in place.

6. Insert the terminal block into the rear of the speaker selector.
7. Connect the left and right channel speaker wires into the terminals on your speaker, taking care to match the polarity.
8. Repeat for the other seven speakers and black terminal blocks.
9. Remove the red colored terminal block from the rear of the speaker selector.
10. Strip approximately 1/4" of insulation from each end of each speaker wire.
11. Using a small flathead screwdriver, loosen the screws on the terminal block.
12. Insert each end of the left channel positive speaker wire into the **L+** terminal and the negative speaker wire into the **L-** terminal, then tighten the screws to secure them in place.
13. Insert each end of the right channel positive speaker wire into the **R+** terminal and the negative speaker wire into the **R-** terminal, then tighten the screws to secure them in place.
14. Insert the terminal block into the rear of the speaker selector.
15. Connect the left and right channel speaker wires into the terminals on your amplifier, taking care to match the polarity.

