Network USB 2.0 Server

Quick Installation Guide Multiple languages Manuals available inside CD









PRINT SERVER USB SERVER VER.1.22

English

Copyright Notice

Copyright Incorporated 2010. All rights reserved.

Disclaimer

Incorporated shall not be liable for technical or editorial errors or omissions contained herein; nor for incidental or consequential damages resulting from furnishing this material, or the performance or use of this product. Incorporated reserves the right to change product specifications without notice. Information in this document may change without notice.

Trademarks

Microsoft, Windows XP, Windows VISTA and Windows 7 are registered trademarks of the Microsoft Corporation. All other brand and product names mentioned herein may be registered trademarks of their respective owners. Customers should ensure that their use of this product does not infringe upon any patent rights. Trademarks mentioned in this publication are sued for identification purposes only and are properties of their respective companies.

WEEE Directive & Product Disposal



At the end of its serviceable life, this product should not be treated as household or general waste. It should be handed over to the applicable collection point for the recycling of electrical and electronic equipment,

or returned to the supplier for disposal.

Table of Content

Environment Setup	01
Introduction	02
Hardware Installation	05
USB LPR Printer Setup on Windows	06
USB LPR Printer Setup on Mac OS X™ (Bonjour)	12
Installation Networking USB Server Utility	16
Networking USB Server Setup on Windows	17
Networking USB Server Featured Functions	24
Connect Automatically for Printing	24
Connect this device when application starts	24
Auto Disconnect Printer/MFP/Storage Device	25
Create a Shortcut on Your Desktop	27
Device Property	28
Control menu	29
Configuration with the Utility	30
Configuration with Web-based UI	32
Removing Networking USB Server Utility from your System	35
MFP-Printer / LPR Printer Compatibility List	36

The Manual for:

Networking USB LPR Print Server (only Support USB LPR Printer)
 Networking USB Server 100M (Support Multi-Function Printers and USB Devices)
 Networking USB Server 1000M (Support Multi-Function Printers and USB Devices)



Environment Setup

The picture above depicts a sample household Network USB Device use environment. To setup the device, simply plug it into the home/Office network under the same router and power it on. Then it could be shared by all the computers on the same network.



Introduction

Thank you for purchasing this Networking USB 2.0 Server that allows any networked computer to share a USB printer, USB Devices. It complies with USB 2.0 specifications (and is backward compatible with USB 1.1), and provides an auto-sensing Ethernet port that works with either 10Base-T, 100Base-T or 1000Base-T networks. This unit also supports multiple protocols and multiple operating systems. The built-in web management feature provides more convenience by allowing the user to configure, monitor and even reset the USB server via a web browser.

The new USB Server enables an external hard drive, flash drive, memory card reader, USB webcam, USB speaker, USB Multi-Function Printer (MFP), or Other USB Devices to be shared on a network. With the versatility afforded by the USB Server, users can now enjoy their favorite multimedia content stored on their computer from anywhere in their home or office use. When connecting USB Server to a wireless router, users can access their multimedia content and USB devices wirelessly. The UPnP technology enables quick and easy setup and configuration in a Windows environment.

We hope that you will enjoy using your USB Server/Print Server and find it to be a useful solution.

Please read this user manual carefully before using. All information on this booklet is subject to change without notice due to technical reasons.



Features

- · Easily connects your USB Printer, USB Device to a network
- · Allows multiple computers to share USB Printer, USB Device on the network
- · Print from any computer on your local network
- Supports DHCP Client and multiple network protocols
- 10Base-T/100Base-T auto-sensing
- 10Base-T/100Base-T/1000Base-T auto-sensing (for 1000M LAN Model)
- Supports Web Management software

Package Contents

for Networking USB Server	for Networking USB LPR Print Server
 Networking USB 2.0 Server 	 Networking USB LPR Print Server
Networking Cable	Networking Cable
Power Adapter 5V	Power Adapter 5V
Installation CD	Installation CD
User Manual	User Manual

If any items are damaged or missing, please contact your dealer.

System Requirements

- Windows 2000/XP/2003/Vista, Windows 7
- Mac OS X 10.2 or later (only support Printer)
- · Device with a USB connection

NOTICE

- 1. Do not use the Network USB Server in the extreme hot, cold, dusty or humid environment.
- 2. Prevent friction with hard objects or it may lead to surface abrasion or hardware damage.
- 3. Avoid the hub falling down from a high place, or it may damage the hardware inside.
- 4. Do not use any alcohol, thinner or benzene to clean the device.
- 5. Please do not use power adaptor with different voltage rating. It will damage or burn the network hub.
- 6. Always check if the device driver is required by some USB peripherals such as Printers, Webcams etc. Please install the device driver on your computer first.
- 7. Some USB devices require a direct connection to PC for optimum performance.
- 8. The Network hub provides 5V power supply which is enough for most USB devices but the power can be in short supply when connecting too many devices like 2.5" external hard disk or connecting other devices with high power consumption simultaneously. Please attach their self-power supply in order to co-work with the network hub properly.

Make sure your network is working and the network cable is connected to the network hub as well.
 You may need to configure the IP address of the network before accessing any USB devices connected with the hub. Please read the user manual.

IMPORTANT NOTE

You can reset your network usb server to default setting by press the 'RESET' button on the back side of the hub.

You can use this solution if you forget your password.



Hardware Installation



- 1. Make sure your network is working properly.
- 2. Connect the USB Printer or other USB devices to the USB ports on the Network USB Server directly or via enclosed USB extension cable.
- Make sure all the driver of the devices connected with the Network USB Server is installed on your computer properly.
- 4. Connect the Network USB Server to the router or Ethernet switch/hub or bridge by enclosed network cable.
- 5. Plug in the power adapter to the Network USB Server.
- 6. Install the driver of the Network USB Server (please find instructions in the next section).

USB LPR Printer Setup on Windows

Provides a straight forward and easy-to-use utility that helps you to set up USB printers connects to LPR Printer server as network printers, Network Printer Wizard. This utility reduces the dozens of steps in setting up network printer via Windows build-in printer setup program to a few point-and-clicks with the mouse. Users no longer need to deal with the confusing IP setting, queue name entering and port configuration.

Install Network Printer Wizard Software

To start the installation, please double click **Setup.exe**, and then click **Networking Printer Wizard for Windows** from autorun setup cover page.

Wait for the installer to run:

Extract Files and install? Click on Yes:





Click on *Finish* to exit installer once installation completes:



The installer creates a shortcut on the Desktop for you:



Network Printer Wizard Setup

- Now we can start setting up your printer. Please click on the Launch Network Printer Wizard icon created on the desktop.
- 2. Please click on *Next* to continue when you see this welcome dialog box.



3. Please select the printer you would like to setup on this list and then Click on *Next*. The number of printers you see on this list depends on the number of printers that are connected to your network. If you only have one printer on the network, you see only one printer on this list. If you don't see any printers, please make sure your printers and USB LPR Printer Server is correctly powered on and connected to the network.

Samed priver you have to de induit of all de door. Samed priver you have to de induit of all door. Samed you have to do door to de door of all door	Browse for Netw	ork Printer	
Saved priver: Compression (Compression (Compression)) Sample's prior (Compression) Preter Information Deception: Semicing ICC+1000 Series Location: UR: Serier	select the prin	er you want to use nom the list below.	-
Cenn FF10.00005 Semeng 14:200 Semes Solido Benezo Sene Solido Pretes Monadon Desoption: Semeng SCI-400 Seres Loadon: UR Server	hared printer:		
Semang N-2000 00001 Elemeng Sci-Hold Semang Sci-Hold Semang Description: Semang SCi-Hold Sema Location: UR: Server	Canon MF3110-00	0015	
Preze Sciences Sciences Preze Sciences Description: Semicing SCI-400 Series Location: URI Serier	Samsung ML-2010	-000001	
Preter Information Description: Semisurg SCI-4000 Series Location: URI: Serier	Satissung SCX-450	0 Series-501201	
Prite Sfanator Description: Sensors SCI-400 Series Locator: URI Serier			
Preter Information Description: Semisurg SCI-4000 Series Location: URI: Server			
Preter Information Description: Samoung SCI-4500 Series Location: L/R Serier			
Printer Information Description: Samoung SCI-4500 Series Location: LPR Server			
Printer Information Destriction: Samoung SCX-4500 Series Location: LPR Server			
Description: Samsung SCX-4500 Series Location: LPR: Server			
Location: LPR Server	Printer Informatic	n	
	Printer Informatic Description:	n Samoung SCX-4900 Series	
	Printer Informatic Description: Location:	n Sanoung SCK-1500 Series LPR Server	
	Printer Informatic Description: Location:	n Samoung SCK-4500 Series LPR Server	



· · Searc

Microsoft Office Documen

On the next dialog box, please select the driver form 4 the list if it's there, and then click on the Next button and go to step 7. Else, read on.

If you can't find the target printer's driver on the list, please insert the disk containing the printer's driver, click on Have Disk ... button then go to step

- You must browse to the folder that contains the 5 driver for your printer and click on OPEN to use it:
- Then, select the driver from the list again and then 6 clik on the Next button. If you didn't select the correct driver, here is the chance for you to verify. Please click on Have Disk ... again to re-select.
- 7. Once you have selected the correct driver from the list, please click on *Finish* button. The wizard might take a minute to setup the network printer for you.



After the printer has been setup correctly, you can 8. see it under Control Panel > Printers:



Documents

Now you can print any document using the printer you just setup:

If you have more than one printer set up, please make sure you have selected the correct printer to print.

NOTE: REMEMBER, THIS SETUP IS A ONE-TIME THING. YOU DO NOT HAVE TO RUN THIS PROCESS EVERY TIME YOU WANT TO PRINT. HOWEVER, OF COURSE, IF YOU REMOVE THE NETWORK PRINTER WIZARD PROGRAM, YOUR PRINTER SETUP WILL NO LONGER WORK.





Remove the Printer Setting

To remove the printer setup, please go to the *Control Panel > Printers* dialog box and remove the printer entry from it.

Simply **Delete** this icon by pressing **Del** key on your keyboard. Then it will be removed from the list of usable printers when you print document.

Remove the Program

To remove the Network Printer Wizard program, please go to *the Control Panel > Add or Remove Programs* (Programs and Features on Windows VISTA)

Then select to remove the program

Then follow the instructions of the installer complete the removing process:

NOTE: Once you remove this problem, you will no longer be able to print using the printers you setup with Network Printer Wizard

Alex particip Voi de la defait de la delas particip presentes en tatas Commenta Location Model Maga Witter Semang SCI-SSB Series Semang SCI-SSB Series
tetan Cammento Location Model

Answer (1) By Sever (1) (1 (Freemond): 1.1 (1) By Sever (1) (1)	1	Currently installed programs:	Show updates	Sort by:	Name	~
Section 2 Section 2 Section 2 Section 2 Section 2 Section 2 Section 2 Section 2 Section 2 Section 2	Change or Remove	Microsoft .NET Framework 1.1				
	Programs	Microsoft .NET Framework 2.0			Size	88.55MB
Benderalized interfaction framework factor bits 1.0 Benderalized interfaction framework factor bits 1.0 Benderalized interfaction Benderalized interfactint Benderali	-	Microsoft Compression Client Pack 1.0 for Windows 3P				
Others See Last See Last Objects Balance Manuel Manue	27	Microsoft User-Mode Driver Framework Feature Pack 1.0				
Alkine for a search financia. Under grounden Alkine for a search financi a search financia. Under grounden Alkine for a search fina	Add News Programs	j∰ Network Printer Wizard			Size	1.004
Composition Composition <thcomposition< th=""> <thcomposition< th=""></thcomposition<></thcomposition<>	-	Cick here for support information.			Used g	crasionally
Barbons To sharp this paging or monote this you annoted, db Oudge or frames. Owayou Ensure If sharp this paging or monote this you annoted, db Oudge or frames. Owayou Ensure Stratege Ensure Stratege Ensure Stratege Ensure Stratege Ensure Stratege Ensure Stratege Strat	0			La	t Lised On	10/29/2008
By Bhuge to b: 56 Hoge to b: 56 Hoge to b: By Bhuge to b: By Bhuge to b: 52.08 2.08 By Bhuge to b: By Bhuge to b: 52.08 2.08 By Bhuge to b: By Bhuge to b: 52.08 2.08 By Bhuge to b: By Bhuge to b: 52.08 2.08 By Bhuge to b: By Bhuge to b: 52.08 5.23 By Bhuge to b: By Bhuge to b: 52.08 5.23	dd Remove	To change this program or remove it from your computer, d	id: Change or Remove.		Change	
	Components	Twitware Tools			Size	16.2848
	0	1 wildPackats EtherPeek AC 2.1			Size	22.50MB
Constant Constan		E Windows Internet Explorer 7			Size	2.6348
Defaults Windows Media Player 11 Size 8.2346 Size 8.2	Access and	Windows Hedia Format 11 runtime			Size	8.23MB
With March and Talk Story (South 1)	Defaults	Windows Media Player 11			Size	8.2346
The second se		Windows 3P Service Pack 3				

USB LPR Printer Setup on Mac OS X[™]

- MAC OS by Apple Inc. comes with a built-in utility very similar to Network Printer Wizard. To start, please go to "System Preferences" on the Dock menu:
- 2. Once you have the "System Preferences" window up, please locate the "Print & Fax" item:

Double click on "*Print & Fax*" to start selecting printer for installation.

 This window shows you the printers that have been installed on your Mac. To install a new printer, please click on the "+" button to select printers.

• 🖯 🖯 👘						
< ⊨ Shc	w All				Q	
Personal						
Tan New				6	6	
lopearance D	ashboard &	Desktop &	Dock	International	Security	Spotlight
	Exposé	Screen Saver				
lardware						
8	0		8	9		4
Bluetooth C	Ds & DVDs	Displays	Energy	Keyboard &	Print & Fax	Sound
			Saver	Mouse		
nternet & Ne	twork	-	-			
()	()	Ø	1			
.Mac	Network	QuickTime	Sharing			
astem						
		(2)	8			
				Canada Citab	Unhannal	
HELOUNIS D	and the latence	Update	apeech	atertage orsk	Access	
ther						
-						
Flip4Mac						
Flip4Mac WMV						
Flip4Mac WMV			Print & Fi	IX		
Flip4Mac WMV	ow All		Print & Fi	1X	Q	
Flip4Mac WMV	ow All		Print & Fi	8x	Q	
Fip4Mac WMV	ow All	Printing	Print & Fi Faxing	ax Sharing	٩	
Flip4Mac WMV	ow All	Printing	Print & Fi	x Sharing	٩	
Flip4Mac WMV	ow All	Printing	Print & Fi	x Sharing	ها	
Fije4Mac WMV	ow All	Printing	Print & Fi	Sharing	٩	
FilpAMac WMV	ow All	Printing	Print & Fi	Sharing No printe	(Q)	
Flip4Mac WMV	Dev All	Printing	Print & Fi	8X Sharing No printe	(Q)	
FighMac WMV	ow All	Printing	Print & Fi	Sharing No printe	C is selected	
FlipMac WMV	ow All	Printing	Print & Fi	Sharing No printe	Q.	
FlotMac WMV	Dw All	Printing	Print & Fi	Sharing No printe	() r is selected Printer Seto	IP)
FlipAMac WMV	Printer	Printing Printing	Print & Fi	No printe	Q	ep)
FlipAMac WMV	ow All Printer	Printing Print Dialog	Print & Fi	No printe Print Queue	Q	

4. Select the printer you would like to setup from the list. The number of printers you see on this list depends on the number of printers that are connected to your network. If you only have one printer on the network, you see only one printer on this list.

> If you don't see any printers, please make sure your printers and Networking LPR Printer Server is correctly powered on and connected to the network

 As you select the printer to install, Bonjour will select the correct printer driver for you and is shown at the "Print Using:" field:

Once you have highlighted the printer to install, click on *Add* button to install it.

2	<u>e</u>	Q.+	
ault Browser	IP Printer		Search
Printer Name			Connection
Canon MP780-	474131	-	Boniour
EPSON PM-A95	0-474133		Bonjour
EPSON Stylus C	45-474131		Bonjour
HP Deskjet 374	0		Bonjour
HP Deskjet 374	0-474131		Bonjour
Lexmark 7300	Series-474131		Bonjour
Name:	EPSON PM-A950-47	4133	
Location:	ESTI Server FPGA_03		
Print Using:	EPSON PM-A950		;

 Once installation is done, you should be able to see this on your "*Print & Fax*" window: You will see that the A950 printer appeared on the available printer list. You can now use this printer for printing your documents or pictures.

> NOTE: REMEMBER, THIS SETUP IS A ONE TIME THING. YOU DO NOT HAVE TO RUN THIS PROCESS EVERY TIME YOU WANT TO PRINT.

 When printing your document, simply select the printer you just setup on the available printer list:

	Printing	axing Sharing	
In Menu Printer		4	
EPSON PN	A-A950-474133		2
		Name: EPSON PM-A	950-474133
		Location: ESTI Server F	PGA_03
		Kind: EPSON PM-A	950 (1)
		Status: Idle	
+ -		Print Queue	Printer Setup
Selected Print	er in Print Dialog:	Last Printer Used	•
Default Paper S	ize in Page Setup:	115 Letter	• (
beneath april a	at an ange becap.		
Click the lock to pr	event further change	15.	
Click the lock to pr	event further change	15. New Cele off (RE 2016)	1 ◯ + ◯ 5.00 m R100 3
Click the lock to pr	event further change	15. ####Contended#11#8215(6) ####111460504	
Click the lock to pr	event further change	5.	C C C C C C C C C C C C C C C C C C C
Click the lock to pr	event further change	5. TransLates,cel (100 (1010)) 0000 (1000 (1000)) 0000 (1000 (1000)) 0000 (1000) (1000) (1000)) 0000 (1000) (1000) (1000) (1000) (1000)) 0000 (1000)	Constant of the second se
Click the lock to pr	event further change	5. mendual pet (182 3010) 500 (102 3010) 500 (102 3010) 500 (102 300) 500 (100 300)	Commentation C
Click the lock to pr	event further change	5	Construction C
Click the lock to pr	event further change	S. B. Construction of the local state of the local	C • C) EXEC • C • C • C • C • C • C • C • C • C •
Click the lock to pr	event further change		Constant and a second and
Click the lock to pr	event further change to the second s	S.	Constraints of the second
Click the lock to pr	event further change	5.	
Click the lock to pr	event further change	s.	
Click the lock to pr			
Click the lock to pr	event further change		
Click the lock to pr			
Click the lock to pr	event further charge	5.	Comparison of the second



Removing the Printer Setting

1. To remove a printer setting, please go to your Printer and FAX again:

Select from the available printer list on the left and then click on the "-" button to remove it.



列印與傳真

 Once removed, the printer will disappear from the list, and when you print document, you will not be able to select it anymore.



Installation Networking USB Server Utility

To start the installation, please double click **Setup.exe**, and then click **USB Server for Windows** from autorun setup cover page.

The installer will automatically install the program.

When done Select **Yes**, I want to restart my computer now and click *Finish* to reboot your computer.

After the installation completes, a shortcut will be created on your Desktop.





Networking USB Server Utility on Windows

To start the Networking USB Server utility, simply double click on the shortcut. This would bring up the main dialog as shown below.



System Firewall

When you start the program for the time, your Windows OS will prompt you for Firewall Access. Please make sure you unblock the software or grant it access, otherwise the program will not work correctly.

Windows XP Firewall Access Alert

Please make sure you "**Unblock**" the program.



Windows Firewall has blocked this program from accepting connections from the Internet or a network. If you recognize the program or trust the publisher, you can unblock it. <u>When should I unblock a program?</u> Windows Vista Firewall Alert

If your system is running Windows Vista, please make sure you "*Unblock*" the program.



Windows 7 Firewall Alert

If your system is running Windows 7, please make sure you click on "*Allow access*" when you see this alert.

Once you have done this once, the system will remember your setting and will not prompt you again next time you run the software.





Main Dialog Box

Once you have start up the program and grant it access through the firewall, you will see this main dialog box.

The main dialog box is consisted of a **Control Menu** (File, Options, View and Help), a tree view in the middle that displays a list of all the server and devices discovered on the network, a **Search** button to get the current status of all USB Servers and devices, and a button that toggles between **Open Web Page** and **Connect Device** depending on the node you select on the tree view. The **Open Web Page** button toggles to Connect Device when a device is highlighted.

Net	working	USB Serve	r				
ile (<u>F</u>)	Options (D) View (¥)	Help (H)				
Device	•		S	Ratus		Information	
	<u>e</u> us	58 Server (192.168.3.18)				
	-	Storage	(ى 🌏	cally Conne	Kingston DataTravler 2.0	
	4	Printer		🚺 Fr	ee	Hewlett-Packard hp LaserJet 1010	
8	<u> </u>	B Server 1	00Mbps (192.)	168.3.19)		
		Storage		2 R	emote Occup	US82.0 Flash Disk	
		Other	(🚺 Fr	ee	ASIX Elec. Corp. AX88178 , This devic	e is behind
			Searc	th .		Open Web Page	

Status of USB Servers and Devices

The device might be in one of the following states and there are different things you can do with it in each of the states. Each status is represented by a specific icon.

Device Online and Free for connection	Device Occupied by yourself
Device Occupied by other user	Device Unsupported
Device on Different Segment	Have Error

Accessing a USB Device

To connect to a USB device, please select it on the tree view and click on Connect Device button or double-click on it. This process might take a few seconds up to a minute, depending on the complexity of the device.

Then you can operate a connected USB device as if it is connected to your PC's USB port directly.

If you select a connected device on the UI, you can see that the *Connect Device* button is changed to *Disconnect Device*:

Clicking on this button releases the selected device for other users. Once you see the icon turns back, the device has been disconnected and other users will then be able to connect to it.

This operation is exactly like when you unplug a USB device from your PC's USB port.







Search

When you are in need of knowing the status of all the servers and devices immediately, use the *Search* button.

Clicking on the **Search** button triggers the program to immediately poll the network for the status of all the servers and devices. The result will be updated to the tree view.

Vevice	Status			Information	
🗃 🕘 USB Server (92.168.3.18)				
- Itorage		Locally Cor	ne	Kingston DataTravler 2.0	
S Printer	0	Free		Hewlett-Packard hp LaserJet 1010	
😑 🕘 USB Server 10	00Mbps (192.168.3	.19)			
— 🤝 Storage	2				
- Cther	0	Free	Re	quest Disconnect Device vice Properties	ind
			Col	nnect this device when application starts rate a Shortcut on Your Desktop	
		_			

Clicking on **YES** to release the device if you are done, click on **Cancel** if you are still using it.

The requesting user will see this message if the occupying user releases the device:

Then the device will be free to connect:



Device Control Request

To request other user to release a Network USB device, use the *Request Disconnect Device* option from the right-click menu.

Of course, this option would only be enabled when the device is currently occupied by someone else. The current occupied user will see this message pops up



If the occupying user click on **Cancel** when received the request, requesting user will see this message instead:

The 3 minute rule is to prevent request spamming. That is, to prevent the current occupying user from being flooded with disconnect request in a short period of time.





System Tray Icon

When minimized to system tray, the Networking USB Server Utility will still be running. Right click on the icon brings up a menu of operations you can still do. As you can see, you can still do Search and Connect. Search is the same. But to connect a storage device, move your mouse to the *"Connect"* option and a list of Network USB Devices will show up. Simply click on the device you would like to connect to connect it.



When connect, a check mark will appear right next to the device on the device list.

To disconnect the device, simply click on it again.

"Open Networking USB Server" option brings up the main GUI. "Exit" option terminates the utility entirely.

Networking USB Server Featured Functions

Connect Automatically for Printing

This is another one of our very convenient functions. What this function does it that when you send a printing task to this printer, it detects this printing task and AUTOMATICALLY connect this printer to print out the document. When the printing task is done, the printer will then be AUTOMATICALLY disconnected so that other users can use it. The user no longer has to manually connect and disconnect the printer. NOTE: This function will be enabled for printers or MFPs that has been installed and used on your PC. For a new printer/MFP, please make sure you have installed it (has been connected via USB port or via USB Server software and worked correctly) on your PC first.



Connect this device when application starts

When enabled, this function automatically connects the target device 15 seconds after the application starts running. If you are using a USB hub or the server has a build-in HUB (4-port USB server has a build-in hub), the device won't be automatically connected if you switch it to another port. If this device is occupied when the application starts, then it will not be connected. If this device is offline when the application starts, then the device will not be connected.



Auto Disconnect Printer/MFP/Storage Device

These functions are there to prevent the case when one user connected a Printer or Storage device but forget to disconnect when he/she is done with the device.

When these two functions are enabled, you will

see this message when you connect a Storage



When the Idle time is up and the device has been disconnected, you get another notification:

NOTE: This function might not work with Storage devices such as pen driver/flash driver. These devices tend to periodically (on a millisecond base) communicate with the OS even when the user is not reading data from it or writing data to it. So it never actually stays "Idle" and will never be automatically disconnected by this function. External USB HDD type storage device does not have this problem.



device or a printer:



Create a Shortcut on Your Desktop

This function creates a shortcut on your Desktop that, when double clicked, starts up Device an application and connects a targeted device at the same time. This function is particularly useful when the functions or one of the functions of the targeted device must work with a specific application, such as a multifunction printer and the photo/picture scanning utility. Normally, if you want to scan with a scanner connected to a USB server. vou must first connect the Scanner with the USB Server software, then run the scan software and start scanning. When you finish with scanning you have to close the scan software and then disconnect the scanner so that other user can use it



However, this shortcut function consolidates these steps into two quick double-click.

Device Property

Clicking on the **Device Property** to bring up the Device Property dialog box.



Networking USB Server

Device Property dialog box displays information of the USB device. If the device is occupied, it also displays the occupying PC name and the IP of the PC occupying it.

This dialog box provides a quite useful function. Check the *Launch a program when this device connects* checkbox and provide the path to that program/utility/application software, then the program/utility/application software would automatically starts up after you connect the device.

This function is particularly useful when the USB device you connect works with an application, such as scanning utility with a multiple function printer.

Device Properties	
Manufac Manufac	cturer : Kingston Aodel : DataTravler 2.0
Device Type	e: Storage
Queue Name	: N/A
Status	: Free
Occupied By PC	: N/A
Occupied By IP	: N/A
Launch an application when t	this device is connected
	Browse
0	ОК



Control menu

File -> The Quit function exits the program.

Options -> Language : You can change the utility's language with this option. The default language would be the same as your system's language.

->Setting Server: Same function as the Setting Server option on the server icon's right click menu. ->Run USBServer When PC Starts Up: This utility automatically runs when your system starts up.

Open Web Page: Brings up the server's configuration web pages.

->Connect Device and Disconnect Device: Connects and disconnects the selected device. ->Request Disconnect Device: When you want to use a device occupied by other user, you can highlight that device and use this function. This sends a message to the occupying user with your request. The occupying user would either release the device or deny the request if s/he is still using the device.

View

The tree view in the main dialog has two display modes: **"Servers and Devices"** mode and **"Devices" Only"** mode. The default setting is **"Devices Only"** mode. You can toggle between these two display modes with the View option on the control menu:



Configuration with the Utility

Networking USB Server utility provides some advanced setting function for users to configure the device to better fit their needs. To bring up the configuration dialog, please RIGHT-CLICK on the device you would like to configure like this,

And select the "Setting Server" option.

You might be prompted to enter password if a password has been set. If not, you will immediately see the dialog.



NOTE: ONLY A FREE DEVICE IS ALLOWED TO BE CONFIGURED, AND TEHEREFORE THIS SETTING OPTION ONLY APPEARS ON FREE NETWORK USB DEVICE



Sever Name: This field allows you change the Server name. Change it whatever you want.

USE DHCP: When this field is checked, your server acquires IP address automatically. Uncheck it and you can enter IP address automatically.

NOTE: You can apply this function to a server under different network segment. **HOWEVER**, some router/switch hub does not allow communication between servers under different segment. In this case, you won't even see the server on a different network segment.

Backup Firmware: this function is a fail-save mechanism for the Update Firmware function. Just browse to where you want to save the backup file and click on Save to save the file.

Update Firmware: update firmware with this function. Use the Browse button to choose the firmware to update. Click on Open to start.

Change Password: Simply enter the new password and enter it again for confirmation. Click on Submit to change.

Restart Server: This button reboots the server. Please note that this function will not work if the server you attempt to reset has a device connected to it and the device is occupied by a user.

Server Configurations
Network Setting :
Server Name : USB Server
IP Address: 192.168.3.20
Subnet: 255.255.0
Connect devices when application starts : Port1 Port2 Port3 Port4 Set
Backup Firmware
Update Firmware
Change Password
Restart Server

Configuration with Web-based UI

We allow the users to configure the settings of the USB Servers via the web-based UI. Select the target server on the tree view and then click on the **Open Web Page** button or the same option on the right-click menu of server icon, to bring up the web-based configuration UI.

Your default web browser will pop up and take you into the web-based configuration UI of the server.

This is the main page of the configuration UI. You can see the important information about the Networking USB Server and the device(s) connected to it. The links at the left-hand side each represents a function. Clicking on "Device Status" brings you back to this page, and the other links take you to pages with different functions.

Networkint USB Server -	Microsoft Internet Expl	orer 📃		×
Ble Edit View Favorites	Toop Rep			1
🔾 Back + 🕤 - 🖹	📓 🏠 🔎 Search	👷 Pavorites 🔣 🔗 · 🌄 🍸 🌾 🛍 🔒		
(dress a) http://192.168.0.22	22/	💌 🔂 Go 🛛 ●3時換 + 🔂法約	4	
NETWORK USB SERVE		THE PRIMERS' AND ACCESS MEDIA. NETWORKING AND WRITELESS		Ī
Device Status	Status			1
N		Server Information		
Network	Server Name	Networking USB 2.0 Server		
Reset Device	Manufacturer	Generic.		
Factory Default	Model	Netwoking USB 2.0 Server		
Password Change	Firmware Version	V. 100.074		
Compatibility List	Server UP-Time	0 days, 0 hours, 0 minutes, 18 seconds.		
		Device 1 Information		
	Device Name	USB Keyboard		
	Link Status	Online		
	Device Status	Ready		
	Current User			
		Device 2 Information		
	Device Name	USB OpticalWheel Mouse		
	Link Status	Online		
	Device Status	Ready		
	Current User			
		Device 3 Information		
	Device Name	C-Media INC. USB Sound Device		
	Link Status	Online		
	Device Status	Ready		1
	Current User			
		Device 4 Information		
	Dendco Nomo	Directed ink MO Tark LIDE PM		×
Done		Internet		



Networking Information/Setting

This page displays the current network setting of the server and provides links to the pages where you can perform special actions. You can change the network setting according to your need. However, please note that if you would like to give this server a static IP, please disable the DHCP option. Once you are done, please click on the "**Submit**" button and reboot the server.

NOTE: A Server with busy device(s) connected is prohibited to be configured to prevent interruption of any on-going tasks.

Networkint US	8 Server - Micros	soft Internet Explorer
ile <u>E</u> dit <u>V</u> iew F <u>a</u> v	orites Tools Help	
3 Back • 🕤 · 🗷	2 🏠 🔑 Search 😒	Favorites 🕙 🍇 🚍 🗉 💭 🚉 🍕 🛧 📲 🗸
(dress 🚵 http://192.10	i8.9.104/	💌 🔁 Go 🛛 🕀 -
NETWORK USB SER\	/er 💿	STARE FRATERS AND ACCESS MEDIA NETWORKING AND WIRELESSLY
Device Status	Network	
Network		
Reset Device		Network Information
Factory Default	IP Setting	Automatic (DHCP)
Password Change	IP Address	192.166.9.104
Compatibility List	MAC Address	00:0e:e6:b7:T2:05
		Network Setting
	DHCP Setting	Enable V
	DHCP Setting	Enable
	DHCP Setting IP Address Subnet Mask	Enable Image: Constraint of the state of th
	DHCP Setting IP Address Subnet Mask Server Name	Enable • 192 168 9 104 255 255 0 Networking USB 20 Server - -
	DHCP Setting IP Address Subnet Mask Server Name Password	Enable

Change Password

Clicking on this link takes you to the password update page below:

To change the password, you must enter current password, input new password and re-input new password for confirmation and then click on **"Submit"**. If you are setting the password for the first time, you don't have to provide current password.

Restart Server

Clicking on this link takes you the page show below:

Networkint USB Server - Microsoft	Internet Explor	er		
Ele Edit View Favorites Tools Help				1
🔾 Back 🔹 🗇 🖹 🖹 🐔 🔑 Search 🔅 Favo	rites 🕘 🌡 📑 🔹	🗆 📖 🖪 🕭 • 🞼 •		
Address an http://192.168.9.104/			💌 🔁 Go	
	E FRINTERS AND ACCE	SS MEDIA NETWORK	NG AND WIRELES	SLY
Device Status Password C	hange			
Network				
Reset Device	Password 0	Change		
Factory Default Current Password	· · · · · · · · · · · · · · · · · · ·	lust Provide If Available'		
Password Change New Password				
Compatibility List Confirm New Password				
	Submit			
8			Internet	

With the *"Restart Server"* button you can reboot the server. However, if there is a password, you must enter it for this function to work. Password is by default blank. So, unless a password is explicitly set, you do not have to enter anything for the reset function to work.

Factory Default

Clicking on this link takes you the page where you can restore the server's settings back to default: Again, the password is not necessary if no password is set. Just leave the field empty and click on the "Factory Default" button to restore the factory default settings.



Removing Networking USB Server Utility from your System

To uninstall Networking USB Server software, please go to Control Panel > Add or Remove Programs

Then please browse through the program list and find **Networking USB Server** program

Please select it and click on the Change/Remove button. Then the uninstaller will start up and prompt you:

When done the installer will prompt you to reboot:

Please select **Finish** to restart your computer. This completely uninstalls the Networking USB Server software from your computer.

dd or R	emove Programs			
5	Currently installed programs: Show updates	Sort by: Nar	ne	~
nange or	13. MIDYIME 410 245 (KRA20191)	Size	2.62MB	^
rograms	倒 MSXML 4.0 SP2 (KB954430)	Size	2.67MB	
2	MSXML 6 Service Pack 2 (KB954459)	Size	1.34MB	
18 - C	😰 Nero 7 Premium			
dd <u>N</u> ew rograms	f Nero Premium 7.5.9.0 Reduced	Size	93.43MB	
-	😰 Network Printer Wizard	Size	1.88MB	
9	18 Networking USB Server	Size	3.54MB	
I/Remove	Click here for support information.		frequently	
mponents	L			=
	To change this program or remove it from your computer, click Change o Remove.	r Change	Remove	
Program	19 NVIDIA Drivers			
cess and	📀 0A 精灵			
relations	A Picture To Icon (remove only)	Size	2.11MB	
	Pixelformer	Size	2.70MB	
	😹 Realtek AC'97 Audio	Size	41.65MB	
	层 SecureCRT 5.1.0 汉化版	Size	18.52MB	
	Setup Factory 6.0	Size	11.93MB	~

MFP-Printer / LPR Printer Compatibility List

No	Drand	Madal Nama	X	Р	Vista	/ 7**
NO	Brand	Model Name	MFP	LPR*	MFP	LPR*
1	Avision	MF3230	Pass	Pass	Pass	Pass
2	BenQ	CM3000	Pass	N/A	Pass	N/A
3	BenQ	CM3500	Pass	N/A	Pass	N/A
4	Brother	HL 2040	Pass	Pass	Pass	Pass
5	Brother	HL 5250DN	Pass	Pass	Pass	Pass
6	Brother	MFC-240C	Pass	Pass	Pass	Pass
7	Brother	MFC-3820cn	Pass	Pass	Pass	Pass
8	Brother	MFC-3320cn	Pass	Pass	-	Pass
9	Brother	MFC-7420	Pass	Pass	Pass	Pass
10	Canon	CanonScan Lide 5.0	N/A	-	N/A	-
11	Canon	ImageClass MF3110	Pass	Pass	Pass	Pass
12	Canon	ImageClass MF3112	-	Pass	-	Pass
13	Canon	ImageClass MF3220	-	Pass	-	Pass
14	Canon	ImageClass MF3222	-	Pass	-	Pass
15	Canon	ImageClass MF4010	Pass	Pass	Pass	Pass
16	Canon	ImageClass MF4150	Pass	Pass	Pass	Pass
17	Canon	iP100	-	Pass	-	Pass
18	Canon	iP1700	Pass	-	Pass	-
19	Canon	iP2500	Pass	Pass	Pass	Pass
20	Canon	iP2600	Pass	-	Pass	-

21	Canon	iP3300	Pass	-	Pass	-
22	Canon	iP3500	Pass	-	Pass	-
23	Canon	iP3600	Pass	-	Pass	-
24	Canon	iP4200	Pass	Pass	Pass	Pass
25	Canon	iP4300	Pass	-	-	-
26	Canon	iP4500	Pass	-	Pass	-
27	Canon	iP4600	Pass	-	Pass	-
28	Canon	iP5000	Pass	Pass	Pass	Pass
29	Canon	iP6700D	Pass	Pass	Pass	Pass
30	Canon	iP7500	Pass	Pass	Pass	Pass
31	Canon	iP90	Pass	Pass	Pass	Pass
32	Canon	iP90v	Pass	Pass	Pass	Pass
33	Canon	iX5000	Pass	-	Pass	-
34	Canon	LBP 1100	Pass	NS	N/A	N/A
35	Canon	LBP 3200	N/A	N/A	Pass	N/A
36	Canon	LBP 3300	N/A	N/A	Pass	N/A
37	Canon	LBP 3700	Pass	Pass	N/A	N/A
38	Canon	MP110	-	Pass	-	Pass
39	Canon	MP130	Pass	Pass	Pass	Pass
40	Canon	MP145	-	Pass	-	Pass
41	Canon	MP150	Pass	Pass	-	Pass
42	Canon	MP160	-	Pass	-	Pass
43	Canon	MP170	-	Pass	-	Pass
44	Canon	MP180	-	Pass	-	Pass

PAGE • 35

PAGE • 37



45	Canon	MP450	Pass	Pass	Pass	Pass
46	Canon	MP460	Pass	Pass	Pass	Pass
47	Canon	MP470	Pass	Pass	Pass	Pass
48	Canon	MP480	Pass	-	Pass	-
49	Canon	MP510	Pass	Pass	Pass	Pass
50	Canon	MP520	Pass	Pass	Pass	Pass
51	Canon	MP540	Pass	-	Pass	-
52	Canon	MP600	Pass	Pass	Pass	Pass
53	Canon	MP610	Pass	Pass	Pass	Pass
54	Canon	MP620	Pass	-	Pass	-
55	Canon	MP630	Pass	-	Pass	-
56	Canon	MP730	Pass	Pass	Pass	Pass
57	Canon	MP780	Pass	Pass	Pass	Pass
58	Canon	MP810	Pass	Pass	-	Pass
59	Canon	MP830	Pass	Pass	Pass	Pass
60	Canon	MP960	Pass	Pass	Pass	Pass
61	Canon	MP970	Pass	Pass	Pass	Pass
62	Canon	MP980	Pass	-	Pass	-
63	Canon	MX308	Pass	Pass	Pass	Pass
64	Canon	MX700	-	Pass	-	Pass
65	Canon	MX7600	Pass	Pass	Pass	Pass
66	Canon	MX850	Pass	Pass	Pass	Pass
67	Canon	Pixus 990i	Pass	Pass	Pass	Pass
68	Canon	Pro9000	Pass	Pass	Pass	Pass
69	Canon	Pro9000Mark II	Pass	-	Pass	-

70	Canon	Pro9500	Pass	Pass	Pass	Pass
71	Canon	Pro9500Mark II	Pass	-	Pass	-
72	Dell	Photo 720	Pass	Pass	Pass	Pass
73	Epson	AL-C900	Pass	Pass	N/A	Pass
74	Epson	EPL-5800	Pass	Pass	Pass	Pass
75	Epson	EPL-6200L	Pass	Pass	Pass	Pass
76	Epson	EPL-N2500	Pass	Pass	N/A	Pass
77	Epson	LP 2500	Pass	Pass	Pass	Pass
78	Epson	Perfection 1270	N/A	-	N/A	-
79	Epson	PM-100	Pass	Pass	-	Pass
80	Epson	PM-3700C	Pass	Pass	Pass	Pass
81	Epson	PM-A840	Pass	Pass	Pass	Pass
82	Epson	PM-A840S	-	Pass	-	Pass
83	Epson	PM-A950	Pass	Pass	Pass	Pass
84	Epson	PM-G4500	Pass	Pass	Pass	Pass
85	Epson	PM-G5300	Pass	Pass	Pass	Pass
86	Epson	PM-G860	Pass	Pass	Pass	Pass
87	Epson	PM-T940	Pass	Pass	Pass	Pass
88	Epson	PM-T960	Pass	Pass	Pass	Pass
89	Epson	PM-T990	Pass	Pass	Pass	Pass
90	Epson	PX-501A	-	Pass	-	Pass
91	Epson	PX-5600	Pass	Pass	Pass	Pass
92	Epson	PX-5800	Pass	Pass	Pass	Pass
93	Epson	PX-A640	Pass	Pass	Pass	Pass
94	Epson	PX-A740	Pass	Pass	Pass	Pass
<u> </u>						

95	Epson	PX-FA700	Pass	Pass	Pass	Pass
96	Epson	PX-V780	Pass	Pass	Pass	Pass
97	Epson	Stylus C43UX	Pass	Pass	Pass	Pass
98	Epson	Stylus C45	Pass	Pass	-	Pass
99	Epson	Stylus C60	Pass	Pass	Pass	Pass
100	Epson	Stylus C61	-	Pass	-	Pass
101	Epson	Stylus C65	-	Pass	-	Pass
102	Epson	Stylus C66	Pass	Pass	-	Pass
103	Epson	Stylus C67	-	Pass	-	Pass
104	Epson	Stylus C90	-	Pass	-	Pass
105	Epson	StylusColor670	Pass	Pass	Pass	Pass
106	Epson	Stylus CX2900	Pass	Pass	Pass	Pass
107	Epson	Stylus CX3500	Pass	Pass	Pass	Pass
108	Epson	Stylus CX3700	-	Pass	-	Pass
109	Epson	Stylus CX3810	Pass	Pass	-	Pass
110	Epson	Stylus CX3900	Pass	Pass	Pass	Pass
111	Epson	Stylus CX4700	Pass	Pass	Pass	Pass
112	Epson	Stylus CX4800	Pass	Pass	-	Pass
113	Epson	Stylus CX4900	Pass	-	Pass	-
114	Epson	StylusCX9300F	Pass	Pass	Pass	Pass
115	Epson	Stylus Photo 1270	Pass	Pass	Pass	Pass
116	Epson	Stylus Photo 2200	Pass	Pass	Pass	Pass
117	Epson	StylusPhoto830	Pass	Pass	-	-
118	Epson	StylusPhoto915	Pass	Pass	Pass	Pass

120	Epson	Stylus R320	Pass	Pass	-	Pass
121	Epson	Stylus RX510	Pass	Pass	Pass	Pass
122	Epson	Stylus RX530	Pass	-	Pass	Pass
123	Epson	Stylus RX590	Pass	-	•	-
124	HP	Deskjet 1125C	Pass	Pass	Pass	Pass
125	HP	Deskjet 1180C	Pass	N/A	N/A	N/A
126	HP	Deskjet 1220C	Pass	N/A	Pass	N/A
127	HP	Deskjet 3745	Pass	Pass	Pass	Pass
128	HP	Deskjet 5652	Pass	Pass	Pass	Pass
129	HP	Deskjet 640C	Pass	Pass	N/A	Pass
130	HP	Deskjet 830C	Pass	N/A	Pass	N/A
131	HP	Deskjet 920C	Pass	-	Pass	-
132	HP	Deskjet D2360	Pass	Pass	Pass	Pass
133	HP	Deskjet D2460	-	Pass	-	Pass
134	HP	Deskjet D3745	Pass	Pass	Pass	Pass
135	HP	Deskjet D4160	Pass	Pass	Pass	Pass
136	HP	Deskjet D4260	-	Pass	-	Pass
137	HP	Deskjet F300	Pass	Pass	Pass	Pass
138	HP	Deskjet F340	-	Pass	-	Pass
139	HP	Deskjet F350	-	Pass	-	Pass
140	HP	Deskjet F370	-	Pass	-	Pass
141	HP	Deskjet F379	-	Pass	•	Pass
142	HP	Deskjet F380	-	Pass	-	Pass
143	HP	Deskjet F4185	Pass	Pass	Pass	Pass
144	HP	LaserJet 1000	Pass	-	N/A	-

PAGE • 38

|--|

145	нР	LaserJet 1010	Pass	Pass	Pass	Pass
146	HP	LaserJet 1015	-	Pass	-	N/A
147	HP	LaserJet 1018	Pass	NS	Pass	NS
148	HP	LaserJet 1020	Pass	N/A	Pass	N/A
149	HP	LaserJet 1022	Pass	Pass	Pass	Pass
150	HP	LaserJet 1160	Pass	NS	Pass	NS
151	HP	LaserJet 2420	Pass	Pass	Pass	Pass
152	HP	LaserJet 2600n	Pass	-	-	-
153	HP	LaserJet 3015	Pass	-	Pass	-
154	HP	LaserJet 3030	Pass	Pass	-	Pass
155	HP	LaserJet 3050	Pass	Pass	Pass	Pass
156	HP	LaserJet 3050z	-	Pass	-	Pass
157	HP	LaserJet 3330	Pass	Pass	Pass	Pass
158	HP	LaserJet 3380	-	Pass	-	NS
159	HP	LaserJet 1005	Pass	N/A	Pass	Pass
160	HP	Officejet4255	Pass	Pass	Pass	Pass
161	HP	Officejet5510	Pass	Pass	Pass	Pass
162	HP	Officejet5610	Pass	Pass	Pass	Pass
163	HP	Officejet6210	Pass	-	Pass	-
164	HP	Officejet7210	Pass	Pass	Pass	Pass
165	HP	OfficejetG85	Pass	-	Pass	-
166	HP	OfficejetL7380	Pass	Pass	Pass	Pass
167	HP	PS 2610	Pass	Pass	Pass	Pass
168	HP	PS 3110	Pass	Pass	Pass	Pass
169	HP	PS 3210	Pass	Pass	Pass	Pass

170	HP	PS 3310	-	Pass	-	Pas
171	HP	PS 335	Pass	Pass	Pass	Pas
172	HP	PS 7830	Pass	Pass	Pass	Pas
173	HP	PS 8030	Pass	Pass	Pass	Pas
174	HP	PS A310	Pass	-	Pass	-
175	HP	PS C3180	Pass	Pass	Pass	Pas
176	HP	PS C5280	Pass	Pass	Pass	Pas
177	HP	PS P1000	Pass	-	N/A	-
178	HP	PS C1210	Pass	Pass	Pass	Pas
179	HP	PS C1315	Pass	Pass	Pass	Pas
180	HP	PS C1350	Pass	Pass	Pass	Pas
181	HP	PS C1402	-	Pass	-	Pas
182	HP	PS C1410	Pass	Pass	Pass	Pas
183	HP	PS C1510	-	Pass	•	Pas
184	HP	PS C1610	Pass	Pass	Pass	Pas
185	HP	PS C2210	Pass	-	Pass	-
186	HP	PS C2410	-	Pass	-	Pas
187	HP	PS C2510	Pass	Pass	Pass	Pas
188	HP	Scanjet4200C	N/A	-	N/A	-
189	HP	Scanjet4370	N/A	-	N/A	-
190	IBM	Infoprint1332	Pass	N/A	N/A	N/A
191	Konica Minota	MC-2430DL	Pass	-	-	-
192	Konica Minota	Page Pro 1350W	Pass	N/A	N/A	N/A
193	Lexmark	E120	Pass	-	Pass	-
194	Lexmark	P4350	Pass	N/A	Pass	N/A

195	Lexmark	P6250	Pass	N/A	Pass	N/A
196	Lexmark	X1270	Pass	NS	Pass	NS
197	Lexmark	X2250	Pass	N/A	Pass	Pass
198	Lexmark	X2650	Pass	NS	Pass	NS
199	Lexmark	X3350	Pass	N/A	Pass	N/A
200	Lexmark	X3470	Pass	NS	Pass	NS
201	Lexmark	X3550	Pass	NS	Pass	NS
202	Lexmark	X4270	Pass	NS	Pass	NS
203	Lexmark	X5150	Pass	-	Pass	-
204	Lexmark	X5470	Pass	N/A	Pass	N/A
205	Lexmark	X5495	Pass	-	Pass	-
206	Lexmark	X6170	Pass	Pass	Pass	Pass
207	Lexmark	X7350	Pass	NS	Pass	NS
208	Lexmark	X8350	Pass	N/A	Pass	N/A
209	Lexmark	Z1350	Pass	-	Pass	-
210	Lexmark	Z43	Pass	Pass	N/A	N/A
211	Lexmark	Z55	Pass	N/A	Pass	N/A
212	Lexmark	Z705	Pass	Pass	Pass	Pass
213	окі	B4350	N/A	N/A	Pass	Pass
214	Samsung	ML-1710	Pass	Pass	Pass	Pass
215	Samsung	ML-1750	Pass	Pass	Pass	Pass
216	Samsung	ML-2010	Pass	Pass	Pass	NS
217	Samsung	SCX 4016	Pass	Pass	Pass	Pass
218	Samsung	SCX 4500	Pass	Pass	Pass	Pass

N/A: This USB Device does not have this function - : Not Tested (Only a certain function of this device was tested)

NS : This function is not supported.

Remark:

 1.** Devices compatibility should be the same on both Windows VISTA and 7, except for the case that the device does NOT support the OS.
 2.MFP - Multi-Function Printer
 3.LPR - Line Printer Remote