

RoHS COMPLIANT												REVISION INFORMATION																	
												Rev.	Rev. Date	Brief Description															
L = 100FT / 250FT / 500FT / 1000FT Green Black White Red Jacket Conductor: (18AWG:41/0.16±0.01) Rip cord Insulation:PVC ① CROSS-SECTION																													
															Conductor		Material/Size		Bare Copper 18AWG (41/0.16±0.01mm)										
															Insulation	Material		FR-PVC											
																Diamter		1.75±0.1mm											
																Nominal Wall		0.27mm											
																Colors		Black .Green.White.Red											
																Elongation		Min 100%											
															Tensile strenght		Min 1.05Kgf/mm²												
															Jacket	Outer Diamter		5.3±0.5mm											
																Min Sheath Thickness		0.36mm											
																Material		FR-PVC											
																Elongation		Min 100%											
																Tensile strenght		Min 1.05Kgf/mm²											
															Filler	Rip cord		250D Nylon*3											
															Electrical Performance	Conductor resistance:<22.0 Ω /1000M(@20° C)													
																Voltage endurance:DC 300V/min													
															1	Cable		Φ5.3[18AWG(41*0.16BC) Φ1.75*4C(Red/Black/White/Green)+Rip cord]Black PVC Jacket, RoHS										1	PCS
															NO.	PART NAME		SPECIFICATION DESCRIPTION										QTY	UNIT

PID	Length	Color	Marking					
13733	100FT	Black	MONOPRICE E470754-PYV (UL) CMP POWER LIMITED CIRCUIT CABLE 18AWG 4C STRANDED	000FT/100FT	002FT/098FT	004FT/096FT	...	098FT/002FT
13734	250FT	Black		000FT/250FT	002FT/248FT	004FT/246FT	...	248FT/002FT
13735	500FT	Black		000FT/500FT	002FT/498FT	004FT/496FT	...	498FT/002FT
16173	1000FT	Black		0000FT/1000FT	0002FT/0998FT	0004FT/0996FT	...	0998FT/0002FT

MONOPRICE

DESCRIPTION :
Monoprice™ Speaker Wire, CMP Rated, 4-Conductor, 18AWG, Black

PID # :
13733, 13734, 13735, 16173

DATE :
UNIT :
FILE NAME:

FT / IN / MM