

RoHS COMPLIANT

REVISION INFORMATION

Rev.	Rev. Date	Brief Description

15 ft

DB25 M

0.6 in

PIN14

PIN1

2.2 in

1.8 in

2.3 in

P1

PIN25

PIN13

1

5

3

4

2.3 in

DB25 F

0.6 in

PIN1

PIN14

2.2 in

P2

PIN13

PIN25

2

* NOTE: All relevant materials are complied with RoHS directive .

P1		P2		2006		P1		P2	
BLACK	1	1	BROWN/BLACK	14	14				
BROWN	2	2	RED/BLACK	15	15				
RED	3	3	ORANGE/BLACK	16	16				
ORANGE	4	4	YELLOW/BLACK	17	17				
YELLOW	5	5	GREEN/BLACK	18	18				
GREEN	6	6	BLUE/BLACK	19	19				
BLUE	7	7	PURPLE/BLACK	20	20				
PURPLE	8	8	GRAY/BLACK	21	21				
GRAY	9	9	WHITE/BLACK	22	22				
WHITE	10	10	PINK/BLACK	23	23				
PINK	11	11	LIGHT GREEN/BLACK	24	24				
LIGHT GREEN	12	12	LIGHT BLUE/BLACK	25	25				
LIGHT BLUE	13	13	SHIELD	SHIELD	SHIELD				

5		BLACK HEAT SHRINK TUBE Ø3.0*30mm	2	
		ALUMINUM FOIL 33*110mm	2	
		MOLDED PE COLOR TRANSPARENT		
		MOLDED PVC BEIGE		
4		NON-UL 25C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 7.0mm, JACKET BEIGE, DRAWING No. EMAL2825C-095	1800mm	
3		MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE	4	
2		DB25 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	
1		DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	1	
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	

MONOPRICE

DESCRIPTION :
Monoprice 15ft DB25 Male-to-Female Serial Extension Cable

PID # :
1594

DATE :
2024/02/23

UNIT :
ft / in

FILE NAME:
1594_PRODUCT