

RoHS COMPLIANT

REVISION INFORMATION

Rev.	Rev. Date	Brief Description

0.35"
(8.8mm)

1.65"(42.0mm)

0.46"
(11.66mm)

Plug

Molding YUS-28

LENGTH

Molding YUS-28

Plug

1

8

P2

PID NO.

Length
(FT)

41032	1ft(12")
41033	3ft(36")
41034	5ft(60")
41035	7ft(84")
41036	10ft(120")
41037	14ft(168")
41038	20ft(240")
41039	50ft(600")
41040	100ft(1200")

MARKING:MONOPRICE CAT.6 U/FTP PATCH CORD CONFORM TO ANSI/TIA-568.2-D IEEE802.3at ▲ 24AWGX4P CMX(UL) E164469-XX

4*Al-Mylar foil

Insulation

Jacket

Conductor

Drain Wire

Conductor	Bare Copper 24AWG	1/0.5±0.008mm
Insulation	Diameter:1.2±0.05mm	
Jacket	PVC	Diameter:6.5±0.3mm

NOTE:

1.ELECTRICAL TEST:
<1> 100% OPEN SHORT & MISS WIRE TEST.
<2> FLUKE CHANNEL LEVEL +POE
<3> CONDUCTOR RESISTANCE: L≤10M 10ΩMAX
10<L≤20M 15ΩMAX
20<L≤40M 25ΩMAX
<4>The function meets the IEEE 802.3bt standard,
maximum length is 60 meters.

MONOPRICE

DESCRIPTION :
Monoprice™ Cat6 PoE Ethernet Patch Cable - 600V, Shielded RJ45, Solid, 550MHz, STP (U/FTP), 24AWG, Black

PID # :
41032 - 41040

DATE :

UNIT :
MM / IN / FT

FILE NAME:

3	MOLD	70P PVC	AR	KG
2	PLUG	8P8C RJ45 50u"Shielded	2	PCS
1	CABLE	CAT.6 U/FTP SLD 24AWGX4P PVC	AR	FT
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT