

RoHS COMPLIANT					VERSION INFORMATION			
					Rev.	Rev. Date	Modified by	Brief Description

VN MARKING:MONOPRICE CAT6A S/FTP CM PATCH CONFORMS TO ANSI/TIA-568.2-D 30AWGX4P (UL) E522879 RoHS

SZ MARKING:MONOPRICE CAT6A S/FTP CM PATCH CONFORMS TO ANSI/TIA-568.2-D 30AWGX4P (UL) E164469-B2 RoHS

NOTE:

1.ELECTRICAL TEST:

<1> 100% OPEN SHORT & MISS WIRE TEST.

<2> PASS FLUKE DSX 8000 ISO PATCH CORD TEST(Randomly test, test rate: 5%)

<3> CONDUCTOR RESISTANCE: L≤10M 10ΩMAX
10<L≤20M 15ΩMAX
20<L≤40M 25ΩMAX

Conductor	30AWG (7/0.10±0.008mmBC)*4P	
INSULATION	Diameter=0.75±0.05mm	
Jacket	PVC	Thickness: Max AVG:0.60 Diameter=4.5±0.15mm

3	RJ45 PLUG	RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE PLUG; SHIELDED NICKEL PLATING		
2	MOLDED	PVC ASSEMBLE BOOT		
1	CABLE	CAT6A S/FTP [30AWG(7/0.05BC±0.008)+AL/MYLAY]*4+AL-MYLAY+ BRAID (16*4/0.08±0.008TC) OD=ø4.5±0.15MM CM PVC JACKET.		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

DESCRIPTION :			
Monoprice™ SlimRun Cat6A 30AWG Patch Cable Component Level			
PID # : 42960-42991			
DATE :		UNIT : MM	FILE NAME:

RoHS COMPLIANT					VERSION INFORMATION			
					Rev.	Rev. Date	Modified by	Brief Description