




P1	1006	P2	
1	_____	1	BROWN
2	_____	2	RED
3	_____	3	ORANGE
4	_____	4	YELLOW
5	_____	5	GREEN
6	_____	6	BLUE
7	_____	7	PURPLE
8	_____	8	GREY
9	_____	9	BLACK
SHIELD	_____	SHIELD	

*NOTE: All relevant materials are complied with RoHS directive .

5	BLACK PVC TUBE $\varnothing 3.0 \times 22\text{mm}$	H7A001-0304K09	2	M304
	ALUMINUM FOIL 33*65mm	A6MA05-0309	2	M309
	MOLDED PE COLOR TRANSPARENT	A5BA02-0280		M280
	MOLDED PVC BEIGE	H1BF01-0304B01		M304
4	NON-UL 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE, DRAWING NO. EMAL2809C-051	H5BL31-0304B01	L-20mm	M304
3	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE	H1RB01-0304B01 A6AA30-0095	4	M95
2	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	A1AA01-0277U09	1	M277
1	DB9 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR	A1AA12-0277U09	1	M277
No.	DESCRIPTION		Q'TY	Supplier

APPROVED		MONOPRICE™		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm	
CHECKED					
DRAWING					
DATE	05/JULY/19	PN	443	UNIT:mm	