

RoHS COMPLIANT					REVISION INFORMATION		
					Rev.	Rev. Date	Brief Description

SZ Marking:MONOPRICE SLIMRUN CAT.6A UTP PATCH CONFORMS TO ANSI/TIA-568.2-D & ISO/IEC 11801▲30AWGX4P CM(UL) E164469-B2 RoHS
VN Marking:MONOPRICE SLIMRUN CAT.6A UTP PATCH CONFORMS TO ANSI/TIA-568.2-D & ISO/IEC 11801▲30AWGX4P CM(UL) E522879 RoHS

orange 2 white/orange	green 3 white/green
blue 1 white/blue	brown 4 white/brown

NOTE:

1.ELECTRICAL TEST:

<1> 100% OPEN SHORT & MISS WIRE TEST.

<2> FLUKE CHANNEL LEVEL 1DB↑

<3> CONDUCTOR RESISTANCE: L≤10M 10ΩMAX
10<L≤20M 15ΩMAX
20<L≤40M 25ΩMAX

Conductor	30AWG (7/0.10±0.008mmBC)*4P	
INSULATION	HDPE Diameter=0.48±0.05mm	
Jacket	PVC	Thickness: Max AVG:0.55 Diameter=3.0±0.15mm

3	RJ45 PLUG	8P8C 50U" GOLD PLATED TWO-PIECE PLUG		
2	MOLDED	PVC ASSEMBLE BOOT		
1	CABLE	CAT6A UTP 4P/30AWG(7/0.10BC) OD=ø3.0±0.15MM PVC JACKET.		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

MONOPRICE

DESCRIPTION :

Monoprice™ Cat6A Ethernet Patch Cable - SlimRun, UTP, 30AWG, 10G, Pure Bare Copper, Snagless RJ45, Black

PID # : 44496 - 44513

DATE :	UNIT : IN / MM	FILE NAME:
--------	----------------	------------