

RoHS COMPLIANT

REVISION INFORMATION		
Rev.	Rev. Date	Brief Description

SZ Marking: MONOPRICE FLEX SERIES TPE CAT.6A UTP PATCH CONFORMS TO ANSI/TIA-568.2-D 24AWGX4P CM(UL) E164469-B2 RoHS

VN Marking: MONOPRICE FLEX SERIES TPE CAT.6A UTP PATCH CONFORMS TO ANSI/TIA-568.2-D 24AWGX4P CM(UL) E522879 RoHS

NOTE:

1.ELECTRICAL TEST:

<1> 100% OPEN SHORT & MISS WIRE TEST.

<2> FLUKE CHANNEL LEVEL 1DB↑

<3> CONDUCTOR RESISTANCE: L≤10M 10ΩMAX
10<L≤20M 15ΩMAX
20<L≤40M 25ΩMAX

PID	Color	Length
44659	black	1ft(12")
44660	black	2ft(24")
44661	black	3ft(36")
44662	black	5ft(60")
44663	black	7ft(84")
44664	black	10ft(120")
44665	black	15ft(180")
44666	black	25ft(300")
44667	black	50ft(600")
44668	black	100ft(1200")

Conductor		24AWG (7/0.20±0.008mmBC)*4P
INSULATION		Diameter=1.00±0.05mm
Jacket	TPE	Thickness: Max AVG:0.60 Diameter=6.0±0.20mm

PA/R	PINOUT		
	P1(T568B)	WIRE	P2(T568B)
2	1	WHT/ORG	1
	2	ORG	2
3	3	WHT/GRN	3
	6	GRN	6
1	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

MONOPRICE

DESCRIPTION :
Monoprice Cat6A Flexible TPE Ethernet Patch Cable - UTP, 24AWG, 500MHz, Pure Bare Copper, Snagless RJ45, Black

PID # :
44668

DATE :
UNIT :
MM

FILE NAME:

3	RJ45	RJ45 PLUG: 8P8C 50U" GOLD PLATED BLACK INDUSRY RATED PLUG;		
2	MOLDED	PVC MOLDED BOOT		
1	CABLE	CAT6A UTP[24AWG(70.20BC±0.008)]*4 OD:Ø6.0±0.02MM TPE JACKET		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT