



Conductor		Bare Copper 24AWG (7/0.20±0.008mmBC)*4P
INSULATION		Thickness:MIN at any point:0.2mm MAX AVG:0.3mm Diameter:0.95±0.06mm
Jacket	PVC	Thickness: MIN at any point:0.50mm MAX AVG:0.70mm Diameter:6.0±0.2MM

5.	RJ45 PLUG	8P8C 50U" GOLD PLATED TWO-PIECE PLUG.		
4.	RJ45 FEMALE	8P8C 3U" GOLD PLATED FEMALE.		
3.	INNER MODEL	LD-PE TRANSPARENT MOLDED BOOT.		
2.	MOLDED	PVC MOLDED BOOT.		
1.	CABLE	CAT6A U/UTP 4P*24AWG(7/0.20±0.008mmBC)+CROSS OD=Ø6.0±0.20MM CM PVC JACKET.		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

	PINOUT		
PA/R	P1(T568B)	WIRE	P2(T568B)
2	1	WHT/ORG	1
	2	ORG	2
3	3	WHT/GRN	3
	6	GRN	6
1	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8



DESCRIPTION :
Monoprice™ Cat6A 1ft, 3ft, 6ft Black U/UTP Ethernet Extension Cable RJ45 Male to Female (with PCB Jack 3μ), 24AWG, Standed Bare Copper, CM PVC Jacket

PID #: 47095, 47096, 47097

DATE :	UNIT :	FILE NAME:
--------	--------	------------