

RoHS COMPLIANT

REVISION INFORMATION		
Rev.	Rev. Date	Brief Description

PIN DEFINE

P1		P2	
A4 B4 A9 B9	red(Vbus)	A4 B4 A9 B9	
A1 B1 A12 B12	Gnd	A1 B1 A12 B12	
A5	blue	A5	
A7	white(D-)	A7	
A6	green(D+)	A6	
A2	blue	B11	
A3	white	B10	
	Gnd		
B11	yellow	A2	
B10	white	A3	
B2	purple	A11	
B3	white	A10	
	Gnd		
A11	orange	B2	
A10	white	B3	
B5	yellow	B5	
A8	red	B8	
B8	black	A8	
	braid		
shell		shell	

Test requirement
100% open, short, mis-wire test.
Insulation resistance: DC300V/10ms,5M ohms (min.).
Contact resistance: 5ohms (max.).
Voltage drop≤0.75V
Speed:≥1800MB/s
resolution:Max 8K/60Hz
Maximum power:240W

6	Case	USB C-type aluminium alloy	2	PCS
5	Outer Molding	TPE plastic	2	PCS
4	Inner Molding	LDPE/natural	2	PCS
3	Type C Plug 2	Nickel plated iron shell, gold plated pin, black rubber core No IC	1	PCS
2	Type C Plug 1	Nickel plated iron shell, gold plated pin, black rubber core belt C	1	PCS
1	Cable	[(26AWG 26/0.08TC+500D Polyester+PP/0.75)*2C+(29AWG 1/0.29BC+PE/0.78)*4P+Drain(32AWG 7/0.08TC)*4C+(30AWG7/0.10TC++PE/0.60)*1P +(32AWG 7/0.08TC+250D Polyester+PP/0.55)*4C +D+AL]+TPE OD5.0mm+PET fiber Braided OD5.5mm	1	PCS
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

DESCRIPTION :
Monoprice USB4 40Gbps Cable 240W EPR, 8K HDR, USB-IF Certified, Braided, Ultra High-Speed, 3ft, Black

PID # : 47632

DATE :

UNIT : MM

FILE NAME: