



PIN DEFINE

P1	Wire Color	P2
A4 B4 A9 B9	red(Vbus)	A4 B4 A9 B9
A1 B1 A12 B12	Gnd	A1 B1 A12 B12
A5	blue	A5
A7	white(D-)	A7
A6	green(D+)	A6
A2	blue	B11
A3	white	B10
A3	Gnd	
B11	yellow	A2
B10	white	A3
B2	purple	A11
B3	white	A10
B3	Gnd	
A11	orange	B2
A10	white	B3
B5	yellow	B5
A8	red	B8
B8	black	A8
B8	braid	
shell	shell	shell



Test requirement
100% open, short, mis-wire test.
Insulation resistance: DC300V/10ms,5M ohms (min.).
Contact resistance: 5ohms (max.).
Voltage drop $\leq$ 0.75V
Speed: $\geq$ 1800MB/s
resolution:Max 8K/60Hz
Maximum power:240W

6	Case	USB C-type aluminium alloy	2	PCS
5	Outer Molding	TPE plastic	2	PCS
4	Inner Molding	LDPE/natural	2	PCS
3	Type C Plug 2	Nickel plated iron shell, gold plated pin, black rubber core No IC	1	PCS
2	Type C Plug 1	Nickel plated iron shell, gold plated pin, black rubber core belt C	1	PCS
1	Cable	[(26AWG 26/0.08TC+500D Polyester+PP/0.75)*2C+(29AWG 1/0.29BC+PE/0.78)*4P+Drain(32AWG 7/0.08TC)*4C+(30AWG7/0.10TC++PE/0.60)*1P +(32AWG 7/0.08TC+250D Polyester+PP/0.55)*4C +D+ALJ]+TPE OD5.0mm+PET fiber Braided OD5.5mm	1	PCS
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT



DESCRIPTION :

Monoprice USB4 40Gbps Cable 240W EPR, 8K HDR, USB-IF Certified, Braided, Ultra High-Speed, 1.5ft, Navy

PID #: 47669

DATE :

UNIT :

MM

FILE NAME: