

RoHS COMPLIANT					VERSION INFORMATION (Vendor)			
					Rev.	Rev. Date	Modified by	Brief Description

P1

A1

B12

A12

B1

6.4

12.2mm (0.48")

22mm (0.87")

6.65mm (0.26")

10ft

9.2mm (0.36")

②③⑥

①

⑦⑥⑤④

DP1.4

III P

8K

P2

11mm(0.43")

20.8mm(0.82")

50.6mm (1.99")

Electrical Test:

1、100% Test(open,short,miss wire)

● Features:

● Support DP1.4 Alt mode, downward compatible with DP1.2 Alt mode

● Support HDMI max 8K/60Hz, 4K/240Hz

● Support Dynamic HDR10+

● Support HDCP1.4 & HDCP2.3 specification

● Support DSC 1.1/1.2a decoder

● Support 8/10/12 bit color depth

● Support pixel format RGB/YCbCr4:4:4:2:2/4:2:0

● Support LPCM audio max 192KHz

● Support HBR audio 768KHz

● Support 3D audio 96KHz

Pin Assignment

	P1		P2
CC	A5		A5
DP	A6		A6
DN	A7		A7
SBU1	A8		A8
Vconn	B5		B5
SBU2	B8		B8
TX1+	A2		A2
TX1-	A3		A3
RX2+	A11		A11
RX2-	A10		A10
TX2-	B2		B2
TX2+	B3		B3
RX1+	B11		B11
RX1-	B10		B10
GND (A1,A12,B1,B12)			A1,A12,B1,B12
Shell			Shell
VBUS (A4,A9,B4,B9)			A4,A9,B4,B9

7	CAP	HDMI DUST CAP	1	PCS
6	MOLDING	TPE~BLACK	VR	PCS
5	SHELL	UTCH8-3M-DPI. 4-SP-PRO (RTD) ~SHELL~ABS~BLACK	1	PCS
4	TUBE	UTCH8-3M-DPI. 4-SP-PRO (RTD) ~PCB-SMT~IC:RTD2175U	1	PCS
3	SHELL	USB-C ~SHELL~ABS~BLACK	1	PCS
2	CONN	USB-C MALE CONNECTOR~SHELL NI PLATED-PIN GOLD~WITH PCB	1	PCS
1	WIRE	USB 3.2~[34AWG (7/0.06TC)+EAM]*4P+34AWG(7/0.06TC)*2C+24AWG(41/0.08TC)*2C+34AWG(7/0.06TC)*4C+AB (75%TC) OD:4.2MM~TPE~BLACK~NO MARKING	3.1	M
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

MONOPRICE

DESCRIPTION :

Monoprice™ USB-C to HDMI Active Cable - 8K60Hz, HDR10+, DSC, 10ft, Black

PID #:

47797

DATE :

UNIT :

FILE NAME: