

RoHS COMPLIANT

| REVISION INFORMATION |           |                   |
|----------------------|-----------|-------------------|
| Rev.                 | Rev. Date | Brief Description |
|                      |           |                   |

PIN19

PIN18

PIN1

PIN2

PID # :

47886

LENGTH (L)

10ft (120")

Mark White : **MONOPRICE** Ultra High Speed HDMI® CABLE With Ethernet E513035 (UL)  
TYPE CL3----- E513034 AWM 20276 80°C 30V VW-1

PIN19

PIN18

PIN1

PIN2

0.36" (9.2mm)

0.41" (10.5mm)

0.18" (4.5mm)

0.79" (20mm)

0.55" (13.9mm)

1.30" (33mm)

PIN Assignment

|       |       |
|-------|-------|
| 1     | 1     |
| 3     | 3     |
| 5     | 5     |
| 4     | 4     |
| 6     | 6     |
| 2     | 2     |
| 7     | 7     |
| 9     | 9     |
| 11    | 11    |
| 10    | 10    |
| 12    | 12    |
| 8     | 8     |
| 14    | 14    |
| 19    | 19    |
| 17    | 17    |
| 13    | 13    |
| 15    | 15    |
| 16    | 16    |
| 18    | 18    |
| SHELL | SHELL |

AL-Foil

AL-Foil+Adhesive-PET

Drain wire

Insulation

Conductor: 28AWG(5P)

Insulation

Conductor: 28AWG(4C)

Braid Shield

Drain wire

Black PVC Jacket OD: ∅7.3mm

NOTES:

1. Test Condition:

(1) 100% OPEN & SHORT TEST;

(2) Insulation Resistance: DC300V 10MΩ(Min) ;

(3) Conductor Resistance: 5Ω/Max.

(4) Hi-Pot:DC 300V/0.1s.

2. The materials meet ROHS standard.

3. HDTV-DVD TEST:8K@60HZ

4. PASS 48G

5. Prop CAP 65

|     |                |                                                                                                                                                                   |     |      |
|-----|----------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|
| 6   | Dust Cap       | HDMI Dust Cap, transparent                                                                                                                                        | 2   | PCS  |
| 5   | OVER MOLD      | PVC 45P Black                                                                                                                                                     |     |      |
| 4   | COPPER FOIL    | Copper foil, W4.5*L30MM (for connector)                                                                                                                           | 2   | PCS  |
| 3   | INTERNAL MODEL | PE                                                                                                                                                                |     |      |
| 2   | CONNECTOR      | HDMI 2.1V AM connector, gold plated, with shielding case                                                                                                          | 2   | PCS  |
| 1   | CABLE          | HDMI UL20276 CABLE 28AWG[(1/0.34BC+FPE0.97)*2C+D1/0.254TC+AL-foil+Adhesive-PET]X5P+(1/0.254BC+HDPE0.55)X4C+AL+D1/0.32BC+B160#/0.12AL-MG+CL3 Black PVC OD7.3±0.2mm | 1   | PCS  |
| NO. | PART NAME      | SPECIFICATION DESCRIPTION                                                                                                                                         | QTY | UNIT |

MONOPRICE

DESCRIPTION :  
Monoprice™ 8k Certified Ultra High Speed HDMI Cable - 8K60Hz, 4K120Hz, 48Gbps, HDR, VRR, CL3 Rated, 10ft, Black

PID # :  
47886

DATE :  
2025/05/13

UNIT :  
IN/MM/FT

FILE NAME:  
47886\_tech\_drawing\_250716