

RoHS COMPLIANT

REVISION INFORMATION

Rev.	Rev. Date	Brief Description

MARKING: FLAT CABLE CAT8 U/FTP 30AWGX4P PATCH CONFORM TO ANSI/TIA-568.2-D & ISO/IEC 11801 ED.1.0 CM(UL) E522879 ▲ RoHS COMPLIANCE

orange 2
white

blue 1
white

green 3
white

brown 4
white

NOTE:

1.ELECTRICAL TEST:

<1> 100% OPEN SHORT & MISS WIRE TEST.

<2> FLUKE CHANNEL LEVEL 1DB↑

<3> CONDUCTOR RESISTANCE: L≤10M 10ΩMAX

10<L≤20M 15ΩMAX

20<L≤40M 25ΩMAX

Conductor	Bare Copper 30AWG (7/0.10±0.008mmBC)*4P	
INSULATION	Thickness:MIN at any point:0.2mm MAX AVG:0.3mm Diameter:0.86±0.06mm	
Jacket	PVC	Thickness: MIN at any point:0.50mm MAX AVG:0.60mm Diameter:2.8±0.15*8.5±0.20MM

3	RJ45 PLUG	RJ45 PLUG: 8P8C 50U" GOLD PLATED TWO-PIECE SHIELDED NICKEL SHORT BODY PLUG;		
2	MOLDED	PVC MOLDED BOOT .		
1	CABLE	CAT.8 U/FTP 3P/30AWG(7/0.10±0.008BC)+[1P/30AWG(7/0.10±0.008BC)+DRAIN(7/0.10mm TC)] OD=2.8±0.15*8.5±0.20mm PVC JACKET		
NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT

MONOPRICE

DESCRIPTION :

Monoprice™ Cat8 Ethernet Patch Cable - Slim, Flat, U/FTP, 30AWG, Molded Boot

PID # : 49176 - 49207

DATE :	UNIT :	FILE NAME:
--------	--------	------------

RoHS COMPLIANT					REVISION INFORMATION		
					Rev.	Rev. Date	Brief Description