



Polarity and Continuity Test	
Dielectric Voltage Withstand Test :2000V /1 Sec	
Electrical Performance (20°C)	
Item	Parameter
Conductor resistance	≤26.0Ω/1000m
Voltage Rating	AC 300/500V

PID	Cable Color	Molding Color	Length (FT)
7670	Black	Black	6±0.1

Pinout		
AS/NZS 3112 (SF-132)	Wire	IEC 60320 C13 (SF-82)
E	YE/GN	E
N	BLUE	N
L	BROWN	L

⑧	Molding	PVC 40P	AR	G
⑦	Sheath	AS/NZS 3112 Three Plug Transparent Colorless Sheath	1	PC
⑥	Housing	Bracket IEC C13 Three Plug Black PBT UL94-V0	1	PC
⑤	Housing	Bracket AS/NZS 3112 Three Plug White PBT UL94-V0	1	PC
④	Terminal	C13Common Terminal,brassy yellow,0.75mm ²	3	PCS
③	Terminal	AS/NZS 3112 Non-Polar, Current Carrying End, 0.75mm ² Nickel Plating	2	PCS
②	Terminal	AS/NZS 3112 Terminal Nickel Plated 0.75mm ²	1	PC
①	Cable	H05VV-F 3G 0.75mm ² x3C Black PVC	1	PC
NO.	PART NAME	SPECIFICATION DESCRIPTION	QT'Y	UNIT

MONOPRICE

DESCRIPTION :
Monoprice Power Cord - AS/NZS 3112 (Australia/New Zealand)
to IEC 60320 C13, H05VV-F 3G 0.75 mm, Black, 6ft

PID # : 7670

DATE : 2023.05.16 UNIT : FT

FILE NAME:
PID_PRODUCT