



Workstream™ by Monoprice™

DisplayPort 1.2a to 4K HDMI, Single Link DVI, and VGA Passive Adapter (Male to Female), Black

Connect a Desktop or Laptop with DisplayPort® to a 4K HDMI®, Single Link DVI™, or VGA Monitor

Connect your DisplayPort®-equipped PC to a 4K HDMI®, Single-Link DVI™, or VGA video display with the Monoprice™ DisplayPort 1.2a to 4K HDMI, Single-Link DVI, and VGA Passive Adapter! This adapter allows you to connect an HDMI, DVI, or VGA display to a DisplayPort video output. It conforms to the DisplayPort 1.2a standard and supports HDMI resolutions up to 4K (3840 x 2160) @30Hz, Single-Link DVI resolutions up to 2560 x 1600 @60Hz, and VGA resolutions up to 1920 x 1080 @60Hz. Being a passive adapter, it is NOT compatible with the AMD® Eyefinity and nVidia® Surround™ multidisplay modes. Note that only one of the three video outputs can be used at any given time.

This unidirectional adapter connects a PC or laptop with DisplayPort to a 4K HDMI, Single-Link DVI, or VGA monitor, display, or projector, but it does not function in reverse (cannot convert HDMI, DVI or VGA to DisplayPort). It features a true 6" cable length with polycarbonate connector housings. The VGA and DVI end panels contain screw holes for secure attachment.

- Conforms to DisplayPort® 1.2a standard
- Supports HDMI resolutions up to 3840 x 2160 @30Hz
- Supports Single-Link DVI resolutions up to 2560 x 1600 @60Hz
- Supports VGA resolutions up to 1920 x 1080 @60Hz
- Plug and Play installation
- Gold-plated connectors improve signal performance
- DisplayPort connector features a locking design with push-button release for a secure connection



COMPATIBLE WITH LEGACY DISPLAYS

The DisplayPort 1.2a to 4K HDMI, Single-Link DVI, and VGA Passive Adapter connects a desktop or laptop with a DisplayPort (DP, DisplayPort++, or DP++) to a monitor, projector, or HDTV with an HDMI, DVI, or VGA input.

Full Specs

P/N	12802
Computer Connection Type	DisplayPort
Display Connection Type	HDMI, Single-Link DVI, and VGA
Maximum Resolution	HDMI: 3840 x 2160 @30Hz
	DVI: 2560 x 1600 @60Hz
	VGA: 1920 x 1080 @60Hz
Cable Length	5.9" (150 mm)
RoHS Compliant	Yes
Packaging Method	Foil bag with header card
Unit Dimensions (LxWxH)	10.4" x 1.8" x 0.6" (265 x 45 x 15 mm)
Unit Package Dimensions (LxWxH)	9.1" x 6.3" x 0.7" (230 x 160 x 17 mm)
Product Weight	2.1 oz (60 g)
Packaged Product Weight	2.8 oz (80 g)
Notes:	



PACKAGE CONTENTS

- 1x DisplayPort 1.2a to 4K HDMI, Single-Link DVI, and VGA Passive Adapter
- 1x User Manual